Home Care Technical Specification

Tool Free Shower Chair

DN7060

Stock Numbers:

DN7060 – Tool-Free Shower Chair

White

Dimensions:


13.317 [338.25] [338.25] [338.25] [338.25] [338.25] [5.363 [390.22] [5.363 [390.22] [8.738 [475.94] [424.16] [6.699 [424.16] [6.699 [424.16] [6.699 [424.16] [5.9.26]

Installation Instructions:

- 1. Slide adjustable legs onto ends of under seat supports, being careful to make sure that the single hole in the top of adjustable leg aligns with the rounded brass studs on the under seat supports.
- 2. Depress brass stud with thumb to allow adjustable leg to slide over it. Brass stud will click into place through hole in adjustable leg.

To adjust length of adjustable legs:

- To adjust length of adjustable legs/height of seat, depress stud to allow leg to move in out of outer post, aligning stud with the hole in post that corresponds with the desired length of adjustable leg. Make sure that stud clicks into place at desired length.
- 2. Test each leg to make sure that all studs have fully clicked into place.
- 3. Grasp seat back by handle and insert bottom tabs into large holes in seat bottom until the tabs snap into place.



INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM

©Copyright Creative Specialties International

Materials:

Tool-Free Shower Chair is made of ABS Plastic, Aluminum, EPDM, and Stainless.





Warning:

TO PREVENT SRIOUS OR FATAL INJURY: Insure product is assembled, adjusted and used properly. FOR USE ONLY BY PERSONS WEIGHING LESS THAN 300 POUNDS. Failure to follow correct assembly and/or adjustment procedures can make the seat unstable. ALL FOUR LEGS MUST BE LOCKED IN PLACE AT THE SAME HEIGHT. DO NOT jump on, stand on or tilt. Contact CSI immediately at 1-800-882-0116 if any components are missing or damaged. Do not modify or substitute any components. FOR QUESTIONS OR ASSISTANCE WITH ASSEMBLY CONTACT CSI AT 1-800-882-9116. Consult healthcare professional for advice and instructions specific to user's needs before use.

