

CODE NUMBER

20021201T

DESCRIPTION

Carbon Offset, ST-2009 Water Closet and SOLIS 8111 Flushometer.

COMPONENTS

 Flushometer: Code 3370000 • Water Closet: Code 2102009

DETAILS

• Flush Volume: 1.6/1.1 gpf (6.0/4.2 Lpf)

 Nominal Dimensions: 25 ¼" × 16 1/125" × 15" (641 × 407 × 381mm)

FLUSHOMETER FEATURES

- Solar Powered. The sensor assembly is powered by a solar cell that will harvest power from artificial indoor light, either incandescent or fluorescent light, and use it as the energy source. The solar cell can provide approximately 100% power with 650 Illuminance (lux).
- Four (4) Size AA Battery Back-up Power Source
- "Low Battery" Flashing LED
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- ADA Compliant Sloan SOLIS® Electronic Dual Flush Solar Powered Infrared Sensor for automatic "No Hands" operation
- Infrared Sensor with Multiple-focused, Lobular Sensing Fields for high and low target detection
- Engineered Metal Cover with replaceable Lens Window
- User friendly three (3) second Flush Delay
- Courtesy Flush® Override Button
- Sweat solder adapter with cover tube and cast wall flange with set
- Fixed Metering Bypass and No External Volume Adjustment to **Ensure Water Conservation**
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop with Free Spinning Vandal Resistant Stop Cap
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed **Bypass**

FIXTURE FEATURES

- White Vitreous China
- · Elongated bowl
- Floor mounted, floor outlet
- Siphon jet flushing action achieves 1000g Map score when used with any Sloan flushometer
- Water spot area: 101/8" x 93/8" (26 cm x 24 cm)
- 1½" I.P.S. top spud inlet
- 21/8" fully glazed trapway
- Closet bolts and caps included
- · Toilet seat not included



COMPLIANCES & CERTIFICATIONS















(cUPC Green Certified, BAA Compliant, CEC Compliant, CalGreen Compliant, Carbon Neutral, EPD, HPD)

DOWNLOADS


- Royal ESS 110/111 Electrical Box Installation Instructions
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance
- Additional Downloads


NOTES

All information contained within this document subject to change without notice.



ROUGH-IN





Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com