

### **CODE NUMBER**

3918126

### **DESCRIPTION**

3.5 gpf, Rough Brass Finish, Single Flush, Metal Oscillating Handle, 8.75 L Dimension, Royal® Concealed Manual Flushometer.

#### **DETAILS**

• Flush Volume: 3.5 gpf (13.2 Lpf)

• Finish: Rough Brass (RB)

Valve: Diaphragm

Valve Body Material: Semi-red Brass

Fixture Type: Water ClosetFixture Connection: Rear

Rough-In Dimension: 16" (406mm)
Spud Coupling: 1 ½" (38mm)

• Supply Pipe: 1" (25mm)

• L Dimension: 8 3/4" (222mm) (8-3/4-LDIM)

• Handle: Metal Oscillating (J)

### **FEATURES**

- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.



## **COMPLIANCES & CERTIFICATIONS**





(UPC Certified, BAA Compliant)

## RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

### **VALVE OPERATING PRESSURE (FLOWING)**

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

# **DOWNLOADS**

- Sloan Stainless Steel Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Flushometers Repair and Maintenance Guide
- Concealed Flushometers Repair and Maintenance Guide
- Additional Downloads

# **NOTES**

All information contained within this document subject to change without notice.

Looking for other variations of the ROYAL 603 product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.



# **ROUGH-IN**

